



vMix PRO Live Production Software
 Up to 8 HD-SDI In / 2 HD-SDI Out
 Professional Audio Input/Output
 Unlimited "Plug and Play" Video Storage

Includes  vMix **Replay**

4 HD-SDI
\$8995 USD

8 HD-SDI From
\$10995 USD



Overview

The power is in your hands to **produce professional live events with extreme portability and maximum features**. With **up to eight full HD camera inputs and 2 HD outputs**, vMix GO allows productions of all sizes. If you **produce house of worship, sports, meetings, training or any other live event**, vMix GO is your go-to rig.

Based on award-winning vMix software, vMix GO gives you nearly unlimited input types, clean transitions, live image adjustment, virtual sets, instant replay and more.



Includes
 rugged
 vinyl roller
 bag

Connection Diagram



4 Removable Hotswap SSD Bays

Balanced Audio XLR/TRS Combo

Up to 8 HD-SDI Inputs
 2 HD-SDI Outputs



Visit our website to locate your nearest reseller

www.vmix.com

Technical Specifications

| | |
|-------------------------------------|---|
| vMix GO 4 | Intel i7 4Ghz, Nvidia GTX 950 2GB, 500GB SSD System Drive, 16GB DDR4 Memory |
| vMix GO Base | Intel i7 4Ghz, Nvidia GTX 950 2GB, 500GB SSD System Drive, 16GB DDR4 Memory, Shuttle Pro Replay Controller |
| vMix GO Plus | Intel i7 4Ghz, Nvidia GTX 950 2GB, 500GB SSD System Drive, 32GB DDR4 Memory, 2TB Storage, Failover Drive, WiFi, Shuttle Pro Replay Controller |
| Video Inputs | Up to 8 simultaneous live HD-SDI video sources w/embedded audio in any combination of HD and SD format |
| Audio Inputs | 1x2 Balanced Neutrik XLR/TRS combo jack, 1/8" Stereo Line-in, 16-channel SDI embedded, compatible with USB (Focusrite, MOTU, M-Audio, etc) |
| Media | Up to 1000 multi-source inputs including video/audio files, PowerPoint (Microsoft Office Req.), DVD, graphics, streams, desktop apps, titles, live social media. Network sources limited only by bandwidth. No artificial DDR players, all imported clips are live and ready to play. |
| Transitions | Cut, Fade, Zoom, Wipe, Slide, Fly, CrossZoom, FlyRotate, Cube, CubeZoom, VerticalWipe, VirtualSlide, Merge and two custom Stinger channels. |
| Mix/Effects | Each input includes 5 "Multi View" overlay channels to create complex Mix/Effects. Add logo bugs, lower thirds, titles, text in combinations to create compelling productions |
| Downstream Keyers | 4 DSKs / overlays with individual transitions, alpha channel and custom scaling/positioning |
| Image Adjustment | Color Correct, Deinterlace, Sharpen, Zoom, Rotate, Pan and Crop any input in real time. All effects are processed in 4:4:4 32bit color space for optimal video quality. |
| Audio Mixer | Independent control and monitoring of all audio sources with Mute, Solo, Follow (Auto Mixing), Delay, EQ, Compressor and Gain |
| Virtual Sets | 6 free virtual sets from Virtualsetworks.com. 5 built-in sets with full motion camera presets and high quality GPU-based chroma key. Easily build your own virtual set using standard tools. |
| Desktop capture | Included screen capture from local/remote PC - Mac Sources |
| Instant Replay | Full four camera instant replay system built in with continuous recording and playback. |
| Controllers | Includes standard keyboard & mouse control with configurable shortcuts/macros. Optional vMix Control Surface available. Built in Web Controller can be used to control vMix from any web connected device on the local network. MIDI supported. |
| Social Media | Integrated application for live or queued insertion of Facebook, Twitter or IRC feeds. Approve and control content from any web-connected device |
| Output | Simultaneous record, stream and output to multiple formats/resolutions |
| Video Outputs | 2x 3G/HD/SD-SDI, 1x HDMI, 1x DisplayPort |
| Audio | 1x2 Balanced Neutrik XLR/TRS combo jack, 1/8" Stereo, 16-channel SDI embedded |
| Recording | AVI, MP4, MPEG-2, MOV and MXF for both Program and ISO recordings with a variety of compression formats available |
| Live Streaming | RTMP streaming to any CDN including USTREAM, Twitch, DaCast, YouTube and more |
| Multiview | Live multiviewer output to secondary display or HD-SDI with configurable layouts and titles, audio meters and tally display |
| Supported Live Video Formats | 2160P (4K), 1080P, 1080i, 720p and SD Multi Format capable. 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 frame rates supported. |
| Physical Dimensions | 14.1" x 16.5" x 7.0" / ~22lbs |